













RESIDENTIAL SECURITY CONTAINER (RSC)



-  UL (Underwriters Laboratories) ANSI/UL 1037 certified, as RSC
-  1 hour factory fire protection.
-  Large 1” diameter chrome plated steel bolts and force resistive handle.
-  1.5” thick construction body and 1.7” thick construction door.
-  UL Certified Electronic lock (other locks options available).
-  1/2” thick Ballistic Steel plate
-  inside the door protecting the locks from frontal attack. 1/4” thick Ballistic Steel plate inside the body protecting the bolts from side attack.
-  Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12 Ga steel body and 3/16 steel door and frame).
-  Sophisticated Spring-Loaded Relocking System is activated and locked when attacked.
-  High quality 30 mm diameter heavy duty hinges.



MODEL	INTERNAL DIMMENSIONS			EXTERNAL DIMMENSIONS			SHELVES	VOLUME	WEIGHT
Name	Height Inch. (CM)	Width Inch. (CM)	Depth Inch. (CM)	Height Inch. (CM)	Width Inch. (CM)	Depth Inch. (CM)	(#)	(ft. ³)	Lbs. Kgs.
RSC 1317	13 (33.02)	17 (43.18)	14.1/2 (36.83)	16 (40.64)	20 (50.80)	20.1/8 (51.12)	1	1.85	355 161
RSC 1713	17 (43.18)	13 (33.02)	14.1/2 (36.83)	20 (50.80)	16 (40.64)	20.1/8 (51.12)	1	1.85	355 161
RSC 2113	21 (53.34)	13 (33.02)	14.1/2 (36.83)	24 (60.96)	16 (40.64)	20.1/8 (51.12)	1	2.29	380 172
RSC 2517	25 (63.50)	17 (43.18)	14.1/2 (36.83)	28 (71.12)	20 (50.80)	20.1/8 (51.12)	1	3.57	490 222
RSC 3717	37 (93.98)	17 (43.18)	14.1/2 (36.83)	40 (101.60)	20 (50.80)	20.1/8 (51.12)	2	5.28	690 313
RSC 5621	56 (142.24)	21 (53.34)	21 (53.34)	59 (149.87)	24 (60.96)	26.3/4 (67.95)	4	14.30	1,140 517

(Depth dimensions do NOT include hinges, lock ad handle. Add 2 inches to depth dimension for standard lock, hinges, and handle. Add up to 3 3/4” for a Push Handle and a 5-Spoke handle)

Authorized Dealer: Lockhart’s Security Phone 1-506-856-5016