



# LOCKHART'S SECURITY

1-506- 856-5016

[www.lockhartssecurity.ca](http://www.lockhartssecurity.ca)



Made in Canada



## Lockhart's Cash Depositories

- ✚ Class B-Rated insurance rating with 1/2 thick high strength steel doors
- ✚ High strength steel body
- ✚ UL certified Group 2M combination lock (other lock options available)
- ✚ Relocking device double locks against burglary attacks
- ✚ Large diameter chrome steel bolts and force resistive handle
- ✚ Hinge side inter-locks from inside to resist hinge removal
- ✚ Deposit tray and front compartment support most deposits
- ✚ Bolt down holes



### SINGLE COMPARTMENT CASH DEPOSITORY

| MODEL       | INTERIOR     |             |             | EXTERIOR     |             |             | VOLUME | WEIGHT |
|-------------|--------------|-------------|-------------|--------------|-------------|-------------|--------|--------|
| Name        | Height (in.) | Width (in.) | Depth (in.) | Height (in.) | Width (in.) | Depth (in.) | (ft.³) | (lbs.) |
| FL20 / RL20 | 12           | 13 ½        | 10 ¼        | 21 3/16      | 14 ¼        | 13 13/16    | 1.04   | 154    |
| FL25        | 15           | 14          | 12          | 25           | 14 ½        | 14 ½        | 2.10   | 185    |
| FL27 / RL27 | 19 ½         | 15 ½        | 15 ½        | 27           | 16          | 19          | 2.71   | 209    |

### DUAL COMPARTMENT CASH DEPOSITORY

|                   |    |      |      |    |    |    |      |     |
|-------------------|----|------|------|----|----|----|------|-----|
| FL-DBL RL-DBL     |    |      |      | 33 | 21 | 21 |      | 345 |
| UPPER COMPARTMENT | 10 | 20 ½ | 17 ½ |    |    |    | 2.08 |     |
| LOWER COMPARTMENT | 14 | 20 ½ | 17 ½ |    |    |    | 2.91 |     |

## Lockhart's B-Rate Safes

- 🔒 1/2" steel pry-resistant recessed door
- 🔒 1/4" continuously welded body
- 🔒 1" chrome plated bolt work
- 🔒 UL Group 2M combination lock (other lock options available)
- 🔒 Lock and relocked protected by hard-plate
- 🔒 Bolt work protected against side attack
- 🔒 Spring loaded relocking device
- 🔒 Solid steel dead bar
- 🔒 Optional Inner Compartments



| MODEL       |              | INTERIOR    |             |              | EXTERIOR    |             |                     | VOLUME | WEIGHT |
|-------------|--------------|-------------|-------------|--------------|-------------|-------------|---------------------|--------|--------|
| Name        | Height (in.) | Width (in.) | Depth (in.) | Height (in.) | Width (in.) | Depth (in.) | (ft. <sup>3</sup> ) | (lbs.) |        |
| OBERON 1313 | 12 ½         | 12 ½        | 6 ¾         | 13           | 13          | 10          | 0.92                | 114    |        |
| OBERON 1614 | 15 ½         | 13 ½        | 10 ¾        | 16           | 14          | 14          | 1.72                | 130    |        |
| OBERON 1717 | 16 ½         | 16 ½        | 15 ¾        | 17           | 17          | 19          | 3.04                | 185    |        |
| OBERON 2020 | 15           | 19 ½        | 19 ½        | 20           | 20          | 20          | 4.92                | 250    |        |
| OBERON 2719 | 26 ½         | 18 ½        | 17 ¾        | 27           | 19          | 21          | 6.02                | 295    |        |
| OBERON 3025 | 29 ½         | 24 ½        | 20 ¾        | 30           | 25          | 24          | 10.12               | 420    |        |

## Lockhart's UL TL 15 LS SAFE

- ✦ UL TL-15 certified
- ✦ 2 hours fire resistance
- ✦ 1.5" diameter steel bolts
- ✦ 2.5" body and 4" door
- ✦ UL certified Group 2M manipulation resistant combination lock with spy proof dial (other lock options available)
- ✦ 1/2" Ballistic Steel plate inside the door protecting the locks
- ✦ Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates
- ✦ Sophisticated glass relock system activates massive re-lockers when
- ✦ attacked Heavy plate steel frame
- ✦ High qualite hinges

\*\*\*Custom interiors available



| MODEL       | INTERIOR     |             |             | EXTERIOR     |             |             | VOLUME | WEIGHT |
|-------------|--------------|-------------|-------------|--------------|-------------|-------------|--------|--------|
| Name        | Height (in.) | Width (in.) | Depth (in.) | Height (in.) | Width (in.) | Depth (in.) | (ft.³) | (lbs)  |
| TL -15 1212 | 12           | 12          | 10          | 17           | 17          | 19 ½        | 0.83   | 430    |
| TL -15 2014 | 20           | 14          | 13 ⅞        | 25           | 19          | 23 ½        | 2.25   | 725    |
| TL -15 2517 | 25           | 17          | 13 ⅞        | 30           | 22          | 23 ½        | 3.41   | 890    |
| TL -15 3219 | 32           | 19          | 16          | 37           | 24          | 25 ¼        | 5.63   | 1177   |
| TL -15 4520 | 45           | 20          | 21          | 50           | 25          | 30 ½        | 10.94  | 1716   |
| TL -15 5520 | 55           | 20          | 21          | 60           | 25          | 30 ½        | 13.37  | 2200   |
| TL -15 6523 | 65           | 23          | 21          | 70           | 28          | 30 ½        | 18.17  | 2585   |
| TL -15 6532 | 65           | 32          | 21          | 70           | 37          | 30 ½        | 25.28  | 3150   |
| TL -15 7240 | 72           | 37          | 21          | 79           | 44          | 30 ½        | 33.27  | 3960   |

## Lockhart's UL TL 30 LS SAFES

- 🔒 UL TL-30 certified
  - 🔒 2-hour fire resistant
  - 🔒 1.5" steel bolts
  - 🔒 2.5" Body and 4" door
  - 🔒 1/2" Ballistic steel hard plate inside the door protecting the locks
  - 🔒 Additional 1/2" ballistic steel plate inside the door
  - 🔒 UL certified Group 2M manipulation resistant combination lock with spy proof dial (other lock options available)
  - 🔒 Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates
  - 🔒 Sophisticated glass relock system activates massive re-locker's when attacked
  - 🔒 Heavy plate steel frame
  - 🔒 High quality hinges
- \*\*\*Custom interiors available



| MODEL        | INTERIOR     |             |             | EXTERIOR     |             |             | VOLUME | WEIGHT |
|--------------|--------------|-------------|-------------|--------------|-------------|-------------|--------|--------|
| Name         | Height (in.) | Width (in.) | Depth (in.) | Height (in.) | Width (in.) | Depth (in.) | (ft.³) | (lbs.) |
| TL - 30 1212 | 12           | 12          | 10          | 17           | 17          | 19 ½        | 0.83   | 450    |
| TL - 30 2014 | 20           | 14          | 13.875      | 25           | 19          | 23 ½        | 2.25   | 755    |
| TL - 30 2517 | 25           | 17          | 13.875      | 30           | 22          | 23 ½        | 3.41   | 930    |
| TL - 30 3219 | 32           | 19          | 16          | 37           | 24          | 25 ½        | 5.63   | 1230   |
| TL - 30 4520 | 45           | 20          | 21          | 50           | 25          | 30 ½        | 10.94  | 1796   |
| TL - 30 5520 | 55           | 20          | 21          | 60           | 25          | 30 ½        | 13.37  | 2280   |
| TL - 30 6523 | 65           | 23          | 21          | 70           | 28          | 30 ½        | 18.17  | 2700   |
| TL - 30 6532 | 65           | 32          | 21          | 70           | 37          | 30 ½        | 25.28  | 3300   |
| TL - 30 7240 | 74           | 37          | 21          | 79           | 44          | 30 ½        | 33.27  | 4250   |

## Lockhart's *UL TL* 30x6 LS SAFE

- ✦ UL TL-30x6 certified
- ✦ 2-hour fire resistant
- ✦ 1.5 "steel bolts
- ✦ 4" body and 4" door
- ✦ 1/2 "Ballistic steel hard plate in all 6 sides of the safes
- ✦ UL certified Group 2M manipulation resistant combination lock with spy proof dial (other lock options available)
- ✦ Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates
- ✦ Sophisticated glass relock system activates massive re-lockers when attacked
- ✦ Heavy plate steel frame
- ✦ High quality adjustable hinges
- ✦ 2 hours fire resistant

\*\*\*Custom interiors available



| MODEL          | INTERIOR     |             |             | EXTERIOR     |             |             | VOLUME              | WEIGHT |
|----------------|--------------|-------------|-------------|--------------|-------------|-------------|---------------------|--------|
| Name           | Height (in.) | Width (in.) | Depth (in.) | Height (in.) | Width (in.) | Depth (in.) | (ft. <sup>3</sup> ) | (lbs)  |
| TL - 30x6 2014 | 20           | 14          | 13 ¾        | 28           | 22          | 25          | 2.25                | 1212   |
| TL - 30x6 2517 | 25           | 17          | 13 ¾        | 33           | 25          | 25          | 3.41                | 1540   |
| TL - 30x6 3219 | 32           | 19          | 16          | 40           | 27          | 27          | 5.63                | 2040   |
| TL - 30x6 4520 | 45           | 20          | 21          | 53           | 28          | 32          | 10.94               | 3020   |
| TL - 30x6 5520 | 55           | 20          | 21          | 63 ½         | 28          | 32          | 13.37               | 3420   |
| TL - 30x6 6523 | 65           | 23          | 21          | 73 ½         | 31          | 32          | 18.17               | 4315   |
| TL - 30x6 6532 | 65           | 32          | 21          | 73 ½         | 40          | 32          | 25.28               | 4850   |
| TL - 30x6 7242 | 74           | 37          | 21          | 80 ½         | 45          | 32          | 33.27               | 5600   |

Sale's & Service



# LOCKHART'S SECURITY

80 Mapleton Rd. Unit 11  
Suite 202  
Moncton, NB, E1C 7W8  
[www.lockhartssecurity.com](http://www.lockhartssecurity.com)

Office: 1 (506) 856-5016  
Fax: 1 (506) 858-8748  
Toll free: 1-877-757-2220  
Email: [lockharts@rogers.ca](mailto:lockharts@rogers.ca)



