



*Lockhart's Security,
Customized to your needs !*

STORMX

- 
- The background of the slide is a grid of metal safes. Each safe has a circular digital keypad lock on its door. The keypad has a small LCD screen at the top and buttons for numbers 0-9, *, and #. The safes are arranged in a grid pattern, with some in the foreground and others receding into the background, creating a sense of depth. The overall color scheme is a light, monochromatic grey.
- U.L certified burglary protection*
 - U.L certified fire protection*
 - U.L certified locks*
 - Heavy duty construction*
 - Double quality control*

Lockhart's UL RATED FIRE SAFES (1 HOUR FIRE RATING)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
FR 13/FR 13E	13	16 1/2	15	7	11 3/4	8 1/2	117	0.40	1	5/8
FR 24/FR 24LGE	24	18	18 1/2	15 1/4	12 1/2	12	209	1.32	1	1 1/8
FR 26/FR 26LGE	24	18	20	14	13	12	231	1.26	1	1 1/8
FR 30/FR 30LGE	30	20	20 3/4	16	13 1/2	13	264	1.63	1	1 1/8
FR 39	39	23 1/2	24	31	18	16	429	5.16	1	1 1/8

* ADD 2" TO EXTERIOR DEPTH TO ACCOMMODATE HINGES, HANDLE AND DIAL

UL Rated 1 Hour Class 350° Fire Label
Special Fire Resistant Foaming Concrete

Model FR 13: Mechanical Combination Lock (4 Numbers)

Models FR 24, FR 26, FR 30: La Gard UL Listed Group 2 Combination Lock

FR13E electronic lock with key override

FR24LGE, FR26LGE, FR30LGE LaGard Basic electronic lock

Auxiliary Key Lock for Dual Custody on all Models

Model FR 13: 2 Locking Bolts (Live)

Models FR 24, FR 26, FR 30: 4 Locking Bolts (Live)

FR24LGE



FR13E



Lockhart's FRONT LOADING DEPOSITORIES FL-208

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
FL 208	19	13.5	15	18.75	13.25	14.75	134.5	2.12	-	1

Door Size 10" x 9.5" (3/8" thick)
High Security LaGard Combination Lock
1/8" Thick Steel Body



FL 208

Lockhart's IN-ROOM HOTEL & LAPTOP SAFES

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
H 17	7	9	7	6 7/8	8 7/8	5	10	0.18	-	3/4
H 20	8	12	8	7 7/8	11 7/8	6 1/2	14	0.35	-	1
H 23	9	16	13	8 7/8	15 7/8	11 1/2	26	0.94	-	1
H 25	10	14	10	9 7/8	13 7/8	8 1/2	22	0.67	1	1

Additional Key Override (2 Keys)
 Built to fit most laptops and tablets
 Powder Coated Black Finish
 Floor or Wall Mounting Options (Hardware Included)
 2 Locking Bolts (Live)
 Concealed Hinges
 Recessed Door
 4 x AA Batteries Included



H 17



H 20



H 25

LAPTOP SAFES

H2048	8	19	14	7 7/8	18 7/8	12	26.4	1.03	-	3/4
-------	---	----	----	-------	--------	----	------	------	---	-----

Electronic Keypad lock with user code and master code
 Electronic Keypad with Tubular Key Override (2 Keys)
 Powder Coated Black Finish
 Floor or Wall Mounting Options (Hardware Included)
 2 Locking Bolts (Live)
 Concealed Hinges
 Recessed Door
 Carpeted Floor
 4 x AA Batteries Included

* ADD 1/2" TO EXTERIOR DEPTH TO ACCOMMODATE HANDLE



Lockhart's BURGLARY AND FIRE SAFES BF SERIES (30 MIN FIRE RESISTANT)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (Single Drawer, in.)			WEIGHT (lbs)
	H	W	D	H	W	D	
BF2020	20	20	20	18	18	14	150
BF3020	30	20	20	28	18	14	178
BF4020	40	20	20	38	18	14	242

LaGard UL Group 2 combination lock
30 minute fire resistance
Heavy duty bolts and handle
Auxiliary Key Lock for Dual Custody on all Models
4 Way Locking Bolts (Live)
1" bolt diameter
Includes sleek wooden shelves for storage convenience
Heavy steel walls with concrete lining make it very secure
Available in blue (BF2020, BF3020, BF4020)



BF2020



BF3020



BF4020

Lockhart's GUN SAFES (1 HOURS FIRE RATING)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
G5930-1	59	40	25	54	36	18	686	20.25	1	1 1/4

* ADD 3" TO EXTERIOR DEPTH TO ACCOMMODATE HINGES, DIAL AND HANDLE

Factory 1 Hour Class 350° Fire Label
 UL Listed Residential Security Container
 California Department of Justice Compliant
 UL Listed Type 1 Electronic Lock
 1 Manager Combination and Optional 1 User Combination
 Three Layers of 1/2" Fireboard in the Door
 Two Layers of 5/8" Fireboard in the Body
 Palusol® Heat Expandable Door Seal
 Composite Door Construction
 12 Gauge (2.05 mm) Body Construction
 Drill Resistant Hard Plate (60-61 Rc)
 Auxiliary Spring-Loaded Relocker Locks a Safe in Case of Brute Force Attack on a Lock
 Four-Way Locking Boltwork
 14 Solid Steel 1-1/4" Diameter Locking Bolts
 Heavy Duty Door Hinges
 30 Long Gun Capacity



Lockhart's GUN SAFES (2 HOURS FIRE RATING)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
G5928-2	59	30	25	54	25 1/2	16	891	12.75	1	2

* ADD 3" TO EXTERIOR DEPTH TO ACCOMMODATE HINGES, DIAL AND HANDLE

Factory 2 Hour Class 350° Fire Label
 UL Listed Residential Security Container
 California Department of Justice Compliant
 UL Listed Type 1 Electronic Lock
 1 Manager Combination and Optional 1 User Combination
 Five Layers of 1/2" Fireboard in the Door
 Four Layers of 1/2" Fireboard in the Body
 Two Palusol® Heat Expandable Door Seals
 Composite Door Construction Includes a 1/4" Solid Steel Plate
 11 Gauge (2.3 mm) Body Construction
 Drill Resistant Hard Plate (60-61 Rc)
 Auxiliary Spring-Loaded Relocker Locks a Safe in Case of Brut e Force Attack on a Lock
 Four-Way Gear Driven Active Boltwork
 14 Massive Solid Steel 2" Diameter Locking Bolts
 Heavy Duty Door Hinges
 28 Long Gun Capacity
 Door Organizer Panel (for Handgun Storage) Included



Lockhart's GUN SAFES (1.5 HOURS FIRE RATING)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
G5930-1.5	59	30	22	54	26	13	651	10.56	1	1 1/4

* ADD 3" TO EXTERIOR DEPTH TO ACCOMMODATE HINGES, DIAL AND HANDLE

Factory 1.5 Hour Class 350° Fire Label
UL Listed Residential Security Container
UL Listed Type 1 Electronic Lock
1 Manager Combination and Optional 1 User Combination
Three Layers of 5/8" Fireboard in the Door
Two Layers of 1/2" Fireboard in the Body
Palusol® Heat Expandable Door Seal
Composite Door Construction
12 Gauge (2.05 mm) Body Construction
Drill Resistant Hard Plate (60-61 Rc)
Auxiliary Spring-Loaded Relocker Locks a Safe in Case of Brute Force Attack on a Lock
Four-Way Locking Boltwork
12 Solid Steel 1-1/4" Diameter Locking Bolts
Heavy Duty Door Hinges
24 Long Gun Capacity




Lockhart's GUN SAFES (0.5 HOURS FIRE RATING)

MODEL	EXTERIOR DIMENSIONS (in.)			INTERIOR DIMENSIONS (in.)			WEIGHT (lbs)	INTERIOR (ft3)	SHELVES	BOLT DIAMETER
	H	W	D	H	W	D				
GR-5920	59	21	17	57	19	12 1/2	358	7.83	1	2

* ADD 3" TO EXTERIOR DEPTH TO ACCOMMODATE HINGES, DIAL AND HANDLE

Factory 0.5 Hour Class 350° Fire Label
 UL Listed Residential Security Container
 Combination lock
 One Layer of 5/8" and one Layer of 1/2" Fireboard in the Door
 One Layer of 5/8" Fireboard in the Body
 Palusol® Heat Expandable Door Seal
 Composite Door Construction
 13 Gauge (1.9 mm) Body Construction
 Drill Resistant Hard Plate (60-61 Rc)
 Auxiliary Spring-Loaded Relocker Locks a Safe in Case of Brute Force Attack on a Lock
 Four-Way Locking Boltwork
 8 Solid Steel 1" Diameter Locking Bolts
 Heavy Duty Door Hinges
 16 Long Gun Capacity





*Lockhart's Security,
customized
to your needs*

DISTRIBUTED BY

**SAFE
MANUFACTURING**

STORMX

Lockhart's Security

80 Mapleton Rd. Unit 11, Suit 202
Moncton ,NB.
E1C 7W8
CANADA

Tel: +1-506-856-5016

Toll-Free: +1-877-757-2220

www.Lockhartssecurity.com